



2508 Bridle Path
 Austin, Texas 78703
 Phone: 512/619-1491
 Fax: 888/437-3192
 email:edwardkmills@gmail.com
 Website: etsincusa.com

May 2014

Industrial Grade **ETS IND™ Guar Gum Powder Specifications**

SPECIFICATION	ETS IND™ 30/35	ETS IND™ 35/40	ETS IND™ 40/45
GRADE	Industrial: 30-35 cPs / 200 Mesh	Industrial: 35-40 cPs / 200 Mesh	Industrial: 40-45 cPs / 200 Mesh
APPEARANCE	Fine Powder	Fine Powder	Fine Powder
CHEMICAL ANALYSIS:	Min - Max	Min - Max	Min - Max
Moisture (%)	0.00 - 7.00	0.00 - 7.00	0.00 - 5.00
Ash (%)	0.00 - 1.00	0.00 - 1.00	0.00 - 1.00
Protein (%)	0.00 - 5.00	0.00 - 5.00	0.00 - 5.00
R.I.A. (%)	0.00 - 5.00	0.00 - 5.00	0.00 - 5.00
pH	6.50 - 8.00	6.50 - 8.00	6.50 - 8.00
GRANULOMETRY:	Min	Min	Min
Thru 200 Mesh (%)	> 97.00	> 97.00	> 97.00
FANN VISCOSITY: <i>FANN 35 Viscometer 300 rpm</i>	10 gm KCL, 2.4 gm G.G.P. 500 ml water, 2 minutes at 2,000 rpm		
3 min (cPs)	34.00 - 36.00	34.00 - 36.00	39.00 - 41.00
60 min (cPs)	39.00 - 41.00	39.00 - 41.00	44.00 - 46.00
PACKAGING:	Jumbo HDPE Bags (2000 lbs); Palletized (double/single stacks), strapped & shrink wrapped, fumigated per USDA or per buyers request		

Notice to Purchaser: The information in this publication is based on tests that we believe are reliable. Your results may vary due to differences in test conditions. You must evaluate whether the product is suitable for your specific intended application. The information above is made with no express or implied warranties. ETS Inc.'s only obligation, and your only remedy, is the replacement of the product if it is shown to be defective when received. In no case will ETS Inc. be liable for any incidental, special, or consequential damages based on breach of warranty or contract, negligence, strict tort, or any other reason.